SELF-PRIMING PUMPS FOR SWIMMING POOLS WITH PREFILTER

The SWIMMEY pumps have been designed to achieve maximum operational reliability in filtering and recirculating water treated with chlorine.

Design Features

- Reinforced technopolymer pump casing and prefilter

 Adjustable two-piece suction and delivery fittings

 Large bowl that may be inspected via screw cap

 Glass-fibre reinforced lexan impeller and diffusor
- resistant to abrasion by sand Mechanical graphite seal with ceramic counterface
- Stainless steel shaft with insulating part Plastic support base for greater pump stability and reduction of vibration
- Screw filter cap with teflon-treated locking O ring

- Enclosed, externally ventilated
 Tropicalised for use in particularly hot and humid
- Level of protection IP X5 with sealed parts
- Class F insulation
- Class F insulation
 Single phase power supply with capacitor permanently activated and thermal protection built into the motor winding
 Three phase power supply with external protection provided by the user
 Self-lubricating ball bearings
 Speed of rotation 2850 rpm
 Suitable for continuous res

- Suitable for continuous use


Usage Limitations


- Type of liquid: swimming pool water treated with chlorine
- Maximum liquid temperature 40°C
- Maximum operation pressure: 2.5 bar Maximum recommended suction height: 3m with foot valve

Applications

Recirculation and filtration of water for swimming pools, spas and bathing pools







Model	Dimensions mm.												
	Α	В	С	D	Е	F	DN	Kg					
SWIMMEY 12	230	35	565	183	280	240	50	8					
SWIMMEY 15	230	35	565	183	280	240	50	8,5					
SWIMMEY 19	240	58	590	183	280	255	50	10,2					

CODE	MODEL	Nominal Power		Absorbed Power		VOLTAGE	Amp.	иF	L/1'	100	150	200	300	350	400	450	500	
		HP	kW	HP	kW	VOLIAGE		-	m ³ /h	6	9	12	18	21	24	27	30	PRICE
N7241230 N7241290	SWIMMEY 12 M SWIMMEY 12 T	0,5	0,37	0,75	0,55	1 ~ 230 V 3 ~ 400 V	2,1 1,7-1	6,3	ad	9	6	2						
N7241240 N7241300	SWIMMEY 15 M SWIMMEY 15 T	0,75	0,5	0,9	0,7	1 ~ 230 V 3 ~ 400 V	3 2,2-1,3	6,3	Discharge Head in meters	11	8,5	4,5						
N7241250 N7241310	SWIMMEY 19 M SWIMMEY 19 T	1	0,75	1,5	1,1	1 ~ 230 V 3 ~ 400 V	4,5 3,3-1,9	16	Disch	15,5	13	10	1,5					